PACCAR PX-9





PROVEN PERFORMANCE. SUPERIOR RESULTS. PERFECT FIT.



The 8.9-liter PACCAR PX-9 engine has one of the highest power-to-weight ratios in its class, with heavy-duty features like replaceable wet liners, roller cam followers, bypass oil filtration and targeted piston-cooling.

Available in both medium and heavy-duty configurations this engine delivers the durability and efficiency needed to lower operating expenses, reduce maintenance and increase productivity.

200

180

160

RATINGS

Engine Horsepower	PEAK TORQUE LB-FT @ RPM	GOVERNED RPM
260	720 @ 1,300	2,200
270	800 @ 1,300	2,200
300°	860 @ 1,300	2,200
330°	1,000 @ 1,400	2,200
345	1,150 @ 1,400	2,100
350	1,000 @ 1,400	2,200
370°	1,250 @ 1,400	2,100
380	1,250 @ 1,400	2,100
380 [†]	1,150 @ 1,400	2,200
400 [‡]	1,250 @ 1,400	2,200
450 [†]	1,250 @ 1,400	2,200

^{*} Also Fire Service Rating

SPECIFICATIONS


Configuration	INLINE 6-CYLINDER	
BORE X STROKE (MM)	114 x 145	
DISPLACEMENT	8.9 liters	
Dry Weight	1,695 lbs.	
OIL SYSTEM CAPACITY	24 U.S. quarts	
Horsepower	260-450 нр	
PEAK TORQUE	720-1,250 lbft.	
GOVERNED SPEED	2,100-2,200 крм	
CLUTCH ENGAGEMENT TORQUE [†]	500 lbft. @ 700 rpm	
BASE WARRANTY [§]	2 Years/250,000 miles/400,000 km	

 $^{^{\}scriptscriptstyle \dagger}$ Determined By Engine Horsepower And Idle Setting

MAINTENANCE INTERVALS

Maintenance Item	Miles	Kilometers
Fuel Filter	15,000	24,000
Oil and Filter	15,000	24,000
COOLANT FILTER (IF EQUIPPED)	15,000	24,000
DEF FILTER	200,000	320,000

Note: Equipment and specifications shown in this brochure are subject to change without notice. Consult with your PACCAR Engine dealer at time of ordering for standard and optional equipment PX-9 is a trademark of PACCAR Inc



HORSEPOWER

ENGINE SPEED (RPM)







PACCAR Inc P.O. Box 1518 Bellevue, WA 98009 2013PACCARPX9SPEC/12



220

200

180

2,200

© 2012 PACCAR Inc

[‡] Fire Service Rating Only

[§]Extended Protection Plans Available